

PACE SYSTEM



PRODUCT INFORMATION

Contents

PACE 1200	2
PACE 600	3
PACE 400	4
PACE 1200 Top Input	5
PACE 1200 Top Output	6
PACE 600 Top Input	7
PACE 600 Top Output	8
Driver 8 Pro	9
Driver 4 Pro	10
Control Panel	11
Connecting Corners	12
Essential Extras	13



Contact us

EMAIL

info@ledsnaps.com

PHONE

+44 (0) 1233 423 360

WEBSITE

www.ledsnaps.com

HEADQUARTERS

Units 21-24
Creative Enterprise Quarter
Javelin Way / Ashford / Kent
TN24 8FN


PRODUCT DATA SHEET

PACE System - 1200



SPECIFICATION DATA

Light source	72 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	18 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LEDsNaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	1212mm x 53mm x 35mm
Weight	1.2kg
Pixel Count	24 Pixels



DESCRIPTION

24 Controllable pixels arranged across 72 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDsNaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.

Up to 20 Pace can be joined together from a single Driver output.

Each Pace locks into the next for safety.

Plug and play installation.



info@ledsnaps.com



+44 (0) 1233 423 360




www.ledsnaps.com

All rights reserved. Improvements changes to specifications, design, and all contents in this data sheet may be made at any time without prior notice.

PRODUCT DATA SHEET

PACE System - 600



SPECIFICATION DATA

Light source	36 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	9 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LEDsNaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	612mm x 53mm x 35mm
Weight	0.75kg
Pixel Count	12 Pixels

DESCRIPTION

12 Controllable pixels arranged across 36 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDsNaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.

Up to 20 Pace can be joined together from a single Driver output.

Each Pace locks into the next for safety.

Plug and play installation.



info@ledsnaps.com



+44 (0) 1233 423 360




www.ledsnaps.com

All rights reserved. Improvements changes to specifications, design, and all contents in this data sheet may be made at any time without prior notice.

PRODUCT DATA SHEET

PACE System - 400



SPECIFICATION DATA

Light source	24 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	6 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LEDSnaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	412mm x 53mm x 35mm
Weight	0.55kg
Pixel Count	8 Pixels

DESCRIPTION

8 Controllable pixels arranged across 24 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDSnaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.

Up to 20 Pace can be joined together from a single Driver output.

Each Pace locks into the next for safety.

Plug and play installation.



info@ledsnaps.com



+44 (0) 1233 423 360




www.ledsnaps.com

All rights reserved. Improvements changes to specifications, design, and all contents in this data sheet may be made at any time without prior notice.

PRODUCT DATA SHEET

PACE System - 1200 Top Input



SPECIFICATION DATA

Light source	72 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	18 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LEDsnaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	1212mm x 53mm x 35mm
Weight	1.25kg
Pixel Count	24 Pixels

DESCRIPTION

24 Controllable pixels arranged across 72 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDSnaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.


Up to 20 Pace can be joined together from a single Driver output.

Each Pace locks into the next for safety.

Plug and play installation.




PRODUCT DATA SHEET



PACE System - 1200 Top Output

SPECIFICATION DATA

Light source	72 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	18 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LED Snaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	1212mm x 53mm x 35mm
Weight	1.25kg
Pixel Count	24 Pixels



DESCRIPTION

24 Controllable pixels arranged across 72 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDSnaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.

Up to 20 Pace can be joined together from a single Driver output.


Each Pace locks into the next for safety.

Plug and play installation.



PRODUCT DATA SHEET

PACE System - 600 Top Input



SPECIFICATION DATA

Light source	36 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	9 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LEDsnaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	612mm x 53mm x 35mm
Weight	1.1kg
Pixel Count	12 Pixels

DESCRIPTION

12 Controllable pixels arranged across 36 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDSnaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.

Up to 20 Pace can be joined together from a single Driver output.


Each Pace locks into the next for safety.

Plug and play installation.



PRODUCT DATA SHEET

PACE System - 600 Top Output



SPECIFICATION DATA

Light source	36 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	9 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LEDsnaps Driver
Power Supply	230 VAC I/P, 12V DC internal
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Dimensions	612mm x 53mm x 35mm
Weight	1.1kg
Pixel Count	12 Pixels

DESCRIPTION

12 Controllable pixels arranged across 36 LEDs for both static and dynamic lighting effects from a custom made LED PCB.

Designed to work exclusively with the LEDSnaps Driver range.

Providing an immersive lighting experience with a hassle free installation.

Powered internally by Mean Well for stable and reliable power.

Up to 20 Pace can be joined together from a single Driver output.

Each Pace locks into the next for safety.


Plug and play installation.



PRODUCT DATA SHEET



PACE System - Driver 8 Pro



SPECIFICATION DATA

Power input	230 VAC
Control interface	Wi-Fi LEDSnaps app
Connections	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Housing	Steel
IP rating	IP20
Power consumption	Less than 3 W
Outputs	8 independent outputs
Data output	SPI / TTL
Operation temp	-20°C to +60°C
Storage temp	-20°C to +70°C
Dimensions	350mm x 450mm x 100mm
Weight	5kg

DESCRIPTION

Designed to work exclusively with the LEDSnaps PACE range.

Driver 8 Pro operates on a 208-240V, 50/60 Hz AC mains power supply.

Up to 20 PACE per output (not exceeding 80 PACE per Driver 8 Pro). For larger installations the Driver 8 Pro can be daisy chained to further Drivers to exceed 80 PACE.

Driver 8 Pro is pre-configured for your layout avoiding the need for costly and time consuming programming.


MCB connection



PRODUCT DATA SHEET



PACE System - Driver 4 Pro



SPECIFICATION DATA

Power input	230 VAC
Control interface	Wi-Fi LEDSnaps app
Connections	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Housing	Steel
IP rating	IP20
Power consumption	Less than 3 W
Outputs	4 independent outputs
Data output	SPI / TTL
Operation temp	-20°C to +60°C
Storage temp	-20°C to +70°C
Dimensions	350mm x 450mm x 100mm
Weight	5kg

DESCRIPTION

Designed to work exclusively with the LEDSnaps PACE range.

Driver 4 Pro operates on a 208-240V, 50/60 Hz AC mains power supply.

Up to 20 PACE per output (not exceeding 40 PACE per Driver 4 Pro). For larger installations our Driver 8 Pro is available.

Driver 4 Pro is pre-configured for your layout avoiding the need for costly and time consuming programming.

MCB connection



info@ledsnaps.com



+44 (0) 1233 423 360




www.ledsnaps.com

All rights reserved. Improvements changes to specifications, design, and all contents in this data sheet may be made at any time without prior notice.

PRODUCT DATA SHEET



PACE System - Control Panel



SPECIFICATION DATA

Operation system	Android 8.1
Touch screen	10-Point capacitive touch
Panel	10.1" LCD panel
Resolution	1280*800
Contrast Ratio	800
Luminance	250cd/m2
Aspect Ratio	16:10
WiFi	802.11b/g/n
Dimensions	273mm x 189mm x 30mm
Weight	0.72kg

DESCRIPTION

The Control Panel has been designed to be intuitive and easy to use.

The tablet has 5 different modes including, house lights, colour picker, slow effects, fast effects and music to light.

*Customisation of the Home Screen is available upon request.

Pre-programmed app interface for seamless scrolling through effects patched for your lighting layout.


A mounting bracket is supplied to mount the tablet to a wall.



PRODUCT DATA SHEET




PACE System - Connecting Corners



SPECIFICATION DATA

Light source	12 LEDs
Typical source life	50,000 hrs
Power requirement	230 VAC
Power consumption	3 W
Colour temperature	RGB
Viewing angle	120°
Housing	Aluminium profile
Cover	PC Diffused cover
IP rating	IP20
Control	LED Snaps Driver
Connection	Integrated 5-pin (Mains & Data)
Listing	CE Certified
Operation temp	-20°C to +40°C
Storage temp	-20°C to +70°C
Weight	0.25kg
Pixel Count	4 Pixels
Dimensions	121mm (arm length) x 53mm x 35mm



DESCRIPTION

Available in Left or Right Flat corner depending on installation design. Possible designs include chevrons, rectangles, squares etc.

An Inside corner is also available to create an up and over effect on a wall and ceiling installation.



PRODUCT DATA SHEET




PACE System - Essential Extras

Mounting Hardware

We offer a complete range of fixing hardware to enable our lights to be installed on a variety of different surfaces.

Infrastructure suspension kit
Flat ceiling kit
Track adapter kit
Existing suspended ceiling kit
Surface mount kit



Audio Kits

If you require the music to light mode we supply two different connection methods to your audio system. Our Line in kit includes everything you need to connect through a 3.5mm socket. Our microphone kit can sample the BPM from the music played in the room.

Cables

To allow the PACE system to be plug-and-play, we use bespoke connectors and cables which are available in the following options:

Starter cables -
2.5m, 5m, 10m and 20m.

Link cables -
0.25m, 1m, 2.5m, 5m.

